



MATERIAL SIZE	
SQUARE MESH SIEVES	RIDOT 2" CRUSHED STONE % FINER
2-1/4 INCHES	100
2 INCHES	90 - 100
1-1/2 INCHES	30 - 55
1-1/4 INCHES	0 - 25
1 INCH	0 - 5

**NOTES:**

1. SHALL BE IN ACCORDANCE WITH SECTION 211 OF THE R.I. STANDARD SPECIFICATIONS.
2. CRUSHED STONE SHALL CONFORM TO THE REQUIRMENTS OF M.01.09 OF THE R.I. STANDARD SPECIFICATIONS.
3. LENGTH SHALL BE 50 FT MINIMUM IN SAND AND GRAVEL AREAS OR 100 FT MINIMUM IN SILT AND CLAY AREAS. LENGTH MAY BE REDUCED IF TRAVEL LENGTH IS LESS.

TOWN OF SOUTH KINGSTOWN DEPARTMENT OF PUBLIC SERVICES

REVISIONS		
NO.	BY	DATE

**CONSTRUCTION ACCESS ENTRANCE**

*WAB*  
TOWN ENGINEER

*John R. Schul*  
DIRECTOR OF PUBLIC SERVICES

12-6-10  
ISSUE DATE

